

AMENDMENTS TO THE CLAIMS

1.(currently amended): A bandwidth control method comprising the steps of:

holding a packet,

counting a packet length of the packet, and

~~reading the held packet at a line bandwidth and controlling a read start timing of a~~
~~next the held packet, based on according to a line bandwidth, a setting bandwidth that is a~~
~~restricted bandwidth, and the packet length, in order that a difference between the line bandwidth~~
~~and a setting bandwidth assumes a packet interval.~~

2.(original): The bandwidth control method as claimed in claim 1, further comprising the steps of notifying a stop of a packet transmission to a packet transmitting side when a number of packets residing in a buffer exceeds a first threshold value, and performing a flow control to notify a restart of the packet transmission to the packet transmitting side when the number of packets residing in the buffer assumes equal to or less than a second threshold value.

3.(original): The bandwidth control method as claimed in claim 2 wherein the flow control is performed only to a subscriber side.

4.(original): The bandwidth control method as claimed in claim 1 wherein the method is performed between an MAC layer process and a physical layer process.

5.(currently amended): A bandwidth control apparatus comprising:

a buffer for holding a packet,

a counter for counting a packet length of the packet, and

~~a read controller for reading the packet at a line bandwidth from the buffer and controlling a read start timing of a next the held packet, based on according to a line bandwidth, a setting bandwidth that is a restricted bandwidth, and the packet length, in order that a difference between the line bandwidth and a setting bandwidth assumes a packet interval.~~

6.(original): The bandwidth control apparatus as claimed in claim 5, further comprising a buffer monitor for notifying a stop of a packet transmission to a packet transmitting side when a number of packets residing in the buffer exceeds a first threshold value, and performing a flow control to notify a restart of the packet transmission to the packet transmitting side when the number of packets residing in the buffer becomes equal to or less than a second threshold value.

7.(original): The bandwidth control apparatus as claimed in claim 6 wherein the buffer monitor performs the flow control only to a subscriber side.

8.(previously presented): A bandwidth control system arranging the bandwidth control apparatus mentioned in claim 5 between an MAC layer controller and a physical layer controller.

9.(original): The bandwidth control system as claimed in claim 8 wherein an interface with each layer controller comprises a standard interface.

10.(original): The bandwidth control apparatus as claimed in claim 5 wherein the packet has a variable length.